



EnGenius® DATASHEET

Wireless Client Bridge/AP/ WDS

ECB-3610S

2.4GHz

802.11 b/g

54 Mbps

ECB-3610S Wireless High Power and High Gain Client Bridge/Access Point/ WDS (wireless distribution system) operates in the 2.4 GHz frequency spectrum supporting the 802.11b (2.4GHz, 11Mbps) and the newer, faster 802.11g (2.4GHz, 54Mbps) wireless standards. It's the best way to add wireless capability to your existing wired network, or to add bandwidth to your wireless installation.



To protect your wireless connectivity, it can encrypt all wireless transmissions through 64/128-bit WEP data encryption and also supports WPA. The MAC address filter lets you select exactly which stations should have access to your network. With the Wireless Multi-Client Bridge/Access Point/WDS, you'll experience the best wireless connectivity available today.

| Features | Benefits |
|---|---|
| High Speed Data Rate Up to 54Mbps | Capable of handling heavy data payloads such as MPEG video streaming |
| High Output Power up to 28dBm | Excellent output power spreads the operation distance |
| IEEE 802.11b/g Compliant | Fully Interoperable with IEEE 802.11b/IEEE802.11g compliant devices |
| Point-to-point, Point-to-multipoint Wireless Connectivity | Let users transfer data between two buildings or multiple buildings |
| Plug and Play | No driver needed, easy and quick to connect your Ethernet device to Wireless |
| WPA/WPA2/ IEEE 802.1x support | Powerful data security |
| Hide SSID (AP Mode) | Avoids unallowable users sharing bandwidth, increases efficiency of the network |
| DHCP Client/ Server | Simplifies network administration |
| WDS (Wireless Distributed System) | Make wireless AP and Bridge mode simultaneously as a wireless repeater |
| MAC address filtering (AP Mode) | Ensures secure network connection |
| Power-over-Ethernet (IEEE802.3af) | Flexible Access Point locations and cost savings |

* Theoretical wireless signal rate based on IEEE standard of 802.11a, b, g chipset used. Actual throughput may vary. Network conditions and environmental factors lower actual throughput rate.

** All specifications are subject to change without notice.

Technical Specifications

Data Rates

1, 2, 5.5, 6, 9, 11, 12, 18, 24, 36, 48, 54 Mbps

Standards

IEEE802.11b/g, IEEE802.3, IEEE802.3u, IEEE802.3af, IEEE802.1f, IEEE802.1x

Compatibility

IEEE 802.11g/ IEEE 802.11b

Power Requirements

Power Supply: 90 to 240 VDC
± 10% (depends on different countries)
Device: 12 V/ 1A

Status LEDs

LAN: Link, WLAN: Link,
Power: on/off

Regulation Certifications

FCC Part 15 B & C,
CE: EN 300328, EN 301489
EN 60950

RF Information

Frequency Band

802.11b/g: U.S., Europe and Japan product covering 2.4 to 2.484 GHz, programmable for different country regulations

Media Access Protocol

Carrier Sense Multiple Access with Collision Avoidance (CSMA/CA)

Modulation Technology

Orthogonal Frequency Division Multiplexing (OFDM)
DBPSK @ 1Mbps
DQPSK @2Mbps
CCK @ 5.5 & 11Mbps
BPSK @ 6 and 9 Mbps
QPSK @ 12 and 18 Mbps
16-QAM @ 24 and 36 Mbps
64-QAM @ 48 and 54 Mbps

Operating Channels

11 for North America
14 for Japan
13 for Europe

Receive Sensitivity (Typical)

- 2.412~2.472G(IEEE802.11g)
6Mbps@ -91dBm;
54Mbps@ -74dBm
- 2.412~2.472G(IEEE802.11b)
11Mbps@ -90dBm

1Mbps@ -95dBm

Available Transmit Power (Typical)

- 2.412~2.472G(IEEE802.11g)
27dBm @6 ~ 24Mbps
25dBm @36Mbps
24 dBm @48Mbps
23dBm @54Mbps
- 2.412~2.472G(IEEE802.11b)
28 dBm@1, 2, 5.5 and 11Mbps

RF Connector

TNC Type (Female Reverse)

Networking

Topology

Ad-Hoc, Infrastructure

Operation Mode

Point-to-Point/ Point-to-Multipoint
Bridge/ AP/ Client Bridge/ WDS

Interface

One 10/100Mbps RJ-45 LAN Port

Security

- IEEE802.1x Authenticator / RADIUS Client (EAP-MD5/TLS/TTLS) Support in AP Mode
- IEEE802.1x Supplicant (EAP-MD5/TLS/TTLS, PEAP) support in Client Bridge Mode
- WPA /WPA2/ Pre Share KEY (PSK) with TKIP/AES
- MAC address filtering (AP only)
- Hide SSID in beacons
- VLAN Pass-through

IP Auto-configuration

DHCP client/server

Management

Configuration

Web-based configuration (HTTP)
Telnet Configuration
SNMP V1, V2c

Firmware Upgrade

Upgrade firmware via web-browser

Environmental

Temperature Range

Operating: 0°C to 45°C (32°F to 113°F)
Storage: -40°C to 70°C (-40°F to 158°F)

Humidity (non-condensing)

5%~95% Typical

Package Contents

One AP/ CB Device
One TNC Dipole Antenna
One Power Adapter
One CAT5 UTP Cable
One Quick Start Guide
One CD-ROM with User's Manual

* Theoretical wireless signal rate based on IEEE standard of 802.11a, b, g chipset used. Actual throughput may vary. Network conditions and environmental factors lower actual throughput rate.

** All specifications are subject to change without notice.

11/14/2007